Package: aesopR (via r-universe)

October 26, 2026

Type Package

Title Tools for Text Analysis of Aesop's Fables

Version 0.1.0

Description Provides a tidy text corpus of Aesop's Fables sourced from the Library of Congress, along with analysis-ready datasets for sentiment, emotion, and linguistic analysis of moral storytelling. The package includes both full narrative texts and word-level representations to support exploratory text analysis and teaching workflows.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Suggests dplyr, knitr, rmarkdown

URL https://davidbrocker.github.io/aesopR/

VignetteBuilder knitr

Repository https://davidbrocker.r-universe.dev

Date/Publication 2026-02-24 16:24:35 UTC

RemoteUrl https://github.com/davidbrocker/aesopr

RemoteRef HEAD

RemoteSha fae4c4ff57dfa7c1148bfb41a5a386da6484a115

Contents

aesops_afinn 2
aesops_bing 3
aesops_fables 4
aesops_tokens 5

Index **7**

aesops_afinn *Aesop's Fables Tokens with AFINN Sentiment Scores*

Description

A token-level dataset of Aesop's Fables joined with the AFINN sentiment lexicon. Each row represents a word from a fable that appears in the AFINN lexicon, along with its associated numeric sentiment score.

Usage

```
data(aesops_afinn)
```

Format

A tibble with one row per token and sentiment match, containing:

fable_id Character identifier for the fable

title Title of the fable

moral The moral or lesson associated with the fable.

word Tokenized word from the fable text

value AFINN sentiment score

Details

The AFINN lexicon assigns integer sentiment values ranging from negative to positive polarity, making this dataset well-suited for aggregated sentiment scoring and comparative analyses across fables.

Source

AFINN sentiment lexicon by Finn Årup Nielsen (2011).

References

Nielsen, F. Å. (2011). *A new ANEW: Evaluation of a word list for sentiment analysis in microblogs*. Proceedings of the ESWC Workshop on Making Sense of Microposts.

See Also

aesops_tokens

`aesops_bing` *Aesop's Fables Tokens with Bing Sentiment Labels*

Description

A token-level dataset of Aesop's Fables joined with the Bing Liu sentiment lexicon. Each row represents a word from a fable that appears in the Bing lexicon, labeled with binary sentiment polarity.

Usage

```
data(aesops_bing)
```

Format

A tibble with one row per token and sentiment match, containing:

fable_id Character identifier for the fable

title Title of the fable

word Tokenized word from the fable text

sentiment Binary sentiment label (`"positive"` or `"negative"`)

Details

The Bing lexicon classifies words as either `"positive"` or `"negative"`, making this dataset useful for polarity-based sentiment summaries and instructional demonstrations.

Source

Bing Liu sentiment lexicon.

References

Hu, M., & Liu, B. (2004). *Mining and summarizing customer reviews*. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining.

See Also

`aesops_tokens`

`aesops_fables` *Aesop's Fables Corpus*

Description

A dataset containing 147 of Aesop's Fables retrieved from the Library of Congress public domain collection.

A dataset containing 147 of Aesop's Fables retrieved from the Library of Congress public domain collection.

Usage

```
aesops_fables
```

```
aesops_fables
```

Format

A tibble with 147 rows and the following variables:

fable_id Character string uniquely identifying the fable (e.g., `"001"`, `"075"`).

title Title of the fable.

full_text Full narrative text of the fable.

moral The moral or lesson associated with the fable.

source_url URL of the original Library of Congress page.

A tibble with 147 rows and the following variables:

fable_id Character string uniquely identifying the fable (e.g., `"001"`, `"075"`).

title Title of the fable.

full_text Full narrative text of the fable.

moral The moral or lesson associated with the fable.

source_url URL of the original Library of Congress page.

Details

Each row represents a single fable and includes metadata, the full narrative text, and the associated moral.

The texts were scraped from https://read.gov/aesop/ and are believed to be in the public domain. Text has been minimally cleaned to preserve original phrasing and narrative structure.

Each row represents a single fable and includes metadata, the full narrative text, and the associated moral.

The texts were scraped from https://read.gov/aesop/ and are believed to be in the public domain. Text has been minimally cleaned to preserve original phrasing and narrative structure.

Source

Library of Congress, "Aesop's Fables"

Library of Congress, "Aesop's Fables"

Examples

```
aesops_fables

if (requireNamespace("dplyr", quietly = TRUE)) {
  aesops_fables |>
    dplyr::filter(fable_id == "075") |>
    dplyr::select(title, moral)
}

aesops_fables

aesops_fables |>
  dplyr::filter(fable_id == "075") |>
  dplyr::select(title, moral)
```

---

aesops_tokens *Tokenized Aesop's Fables*

Description

A tidy token-level dataset derived from aesops_fables, where each row represents a single word token from a fable.

A tidy token-level dataset derived from `aesops_fables`, where each row represents a single word token from a fable.

Usage

```
aesops_tokens

aesops_tokens
```

Format

A tibble with one row per word token and the following variables:

fable_id Character string identifying the source fable.

word Lowercase word token extracted from the fable text.

word_count Total number of words in the source fable.

source_url URL of the original fable text.

A tibble with one row per word token and the following variables:

fable_id Character string identifying the source fable.

title Title of the fable

moral The moral or lesson associated with the fable.

word Lowercase word token extracted from the fable text.

Details

This dataset is intended for text analysis tasks such as sentiment analysis, n-gram modeling, and word frequency analysis.

Tokens were generated using `tidytext::unnest_tokens()`. Stop words have not been removed, allowing users full flexibility in preprocessing decisions.

This dataset is intended for text analysis tasks such as sentiment analysis, n-gram modeling, and word frequency analysis.

Tokens were generated using `tidytext::unnest_tokens()`. Stop words have not been removed, allowing users full flexibility in preprocessing decisions.

See Also

aesops_fables

`aesops_fables`

Examples

```
aesops_tokens

if (requireNamespace("dplyr", quietly = TRUE)) {
  aesops_tokens |>
    dplyr::count(word, sort = TRUE)
}

aesops_tokens

aesops_tokens |>
  dplyr::count(word, sort = TRUE)
```

Index

∗ **datasets**
aesops_afinn, 2
aesops_bing, 3
aesops_fables, 4
aesops_tokens, 5

aesops_afinn, 2
aesops_bing, 3
aesops_fables, 4, *5*, *6*
aesops_tokens, *2*, *3*, 5